

TERMOARREDO®



TERMOARREDO® RANGE

Steel towel rails

The range of towel rails by Sira Industries includes several models combining heating function to different needs of various rooms (bathrooms, kitchens, saunas, hotels, communities, etc.).

Made of high quality carbon steel, these radiators can become real pieces of furniture, elegant, refined and easy to integrate in any environment.

Simply, Flex Chrome and Flex White have been designed for granting safeness against fires and home accidents using rounded and smooth profiles.

These radiators can be guaranteed for 2 years because the most updated techniques in welding, assembling and working are used.

Termoarredo® range is composed by:

Simply, steel towel rails white colored: simple and elegant.

Flex White, white colored with rounded and smooth surfaces: design without compromise.

Flex Chrome, chromed finished: the very top as for aesthetics and functionality.

A special range of towel rails, named "**Private Collection**" is available by request and order only. It has original shapes and exclusive finishings.

SIMPLY

TERMOARREDO®



2 ANNI-YEARS
GARANZIA
WARRANTY

COLORE DI SERIE BIANCO
WHITE COLOR
RAL 9010



DATI TECNICI / TECHNICAL DATA

Modello Model	Altezza Total height [mm]	Larghezza Width [mm]	Interasse Distance between centers [mm]	Resa termica Heat output EN442 $\Delta t = 50 \text{ K}$	Resa termica Heat output EN442 $\Delta t = 30 \text{ K}$
Simply	800	450	400	322	174
Simply	1200	450	400	507	274
Simply	1400	450	400	623	337
Simply	1600	450	400	831	449
Simply	800	500	450	366	198
Simply	1200	500	450	564	305
Simply	1400	500	450	663	358
Simply	1600	500	450	911	492
Simply	800	550	500	427	231
Simply	1200	550	500	668	361
Simply	1400	550	500	785	424
Simply	1600	550	500	992	536
Simply	800	600	550	454	245
Simply	1200	600	550	714	386
Simply	1400	600	550	839	453
Simply	1600	600	550	1062	574

• Pressione massima d'esercizio è di 600 kPa (6 bar)
 • I valori di resa termica sono conformi alla norma europea UNI EN 442-2
 • The maximum operating pressure is 600 kPa (6 bar)
 • Thermal output comply with the European standard UNI EN 442-2



FLEX WHITE

TERMOARREDO®



2 ANNI-YEARS
GARANZIA
WARRANTY

COLORE DI SERIE BIANCO
WHITE COLOR
RAL 9010



• Pressione massima d'esercizio è di 600 kPa (6 bar)
 • I valori di resa termica sono conformi alla norma europea UNI EN 442-2
 • The maximum operating pressure is 600 kPa (6 bar)
 • Thermal output comply with the European standard UNI EN 442-2

DATI TECNICI / TECHNICAL DATA

Modello Model	Altezza Total height [mm]	Larghezza Width [mm]	Interasse Distance between centers [mm]	Resa termica Heat output EN442 $\Delta t = 50 \text{ K}$	Resa termica Heat output EN442 $\Delta t = 30 \text{ K}$
Flex White	800	450	400	324	175
Flex White	1200	450	400	510	276
Flex White	1400	450	400	626	338
Flex White	1600	450	400	834	451
Flex White	800	500	450	368	200
Flex White	1200	500	450	567	307
Flex White	1400	500	450	665	361
Flex White	1600	500	450	915	494
Flex White	800	550	500	429	233
Flex White	1200	550	500	671	363
Flex White	1400	550	500	788	425
Flex White	1600	550	500	995	538
Flex White	800	600	550	456	247
Flex White	1200	600	550	717	388
Flex White	1400	600	550	841	455
Flex White	1600	600	550	1065	576

FLEX CHROME

TERMOARREDO®



2 ANNI-YEARS
GARANZIA
WARRANTY

COLORE DI SERIE
CROMATO
CHROME



DATI TECNICI / TECHNICAL DATA

Modello Model	Altezza Total height [mm]	Larghezza Width [mm]	Interasse Distance between centers [mm]	Resa termica Heat output EN442 $\Delta t = 50\text{ K}$	Resa termica Heat output EN442 $\Delta t = 30\text{ K}$
Flex Chrome	800	450	400	227	123
Flex Chrome	1200	450	400	376	203
Flex Chrome	1400	450	400	446	241
Flex Chrome	1600	450	400	569	307
Flex Chrome	800	500	450	253	137
Flex Chrome	1200	500	450	397	215
Flex Chrome	1400	500	450	490	265
Flex Chrome	1600	500	450	621	335
Flex Chrome	800	550	500	277	150
Flex Chrome	1200	550	500	450	243
Flex Chrome	1400	550	500	535	289
Flex Chrome	1600	550	500	672	363
Flex Chrome	800	600	550	302	163
Flex Chrome	1200	600	550	475	257
Flex Chrome	1400	600	550	560	302
Flex Chrome	1600	600	550	697	375

• Pressione massima d'esercizio è di 600 kPa (6 bar)
 • I valori di resa termica sono conformi alla norma europea UNI EN 442-2
 • The maximum operating pressure is 600 kPa (6 bar)
 • Thermal output comply with the European standard UNI EN 442-2